



## THERMAL ANALYTICS SECURITY CAMERA

# FLIR FB-SERIES ID™

The FB-Series ID combines best-in-class thermal image detail and high-performance onboard video analytics in a single, and affordable bullet-type form factor that is ideal for perimeter intrusion detection. FB-Series ID cameras feature on-board video analytics capable of classifying human or vehicular intrusions, making them an ideal choice for monitoring commercial and industrial perimeters. Easy to set up, FB-Series ID cameras provide reliable detection & classification with very few false alarms rates without human intervention. Equipped with FLIR's award-winning thermal technology, FB-Series ID is designed to deal with challenging environments or bad weather, and can operate in complete darkness.

## SPECIFICATIONS

	FB 3xx ID-Series	FB 6xx ID-Series
<b>Image</b>		
Array Format (NTSC)	320 x 240	640 x 480
Detector Type	Long-Life, Uncooled VOx Microbolometer	
Effective resolution	76,800 pixels	307,200 pixels
Thermal frame rate	NTSC: 30 Hz / PAL: 25 Hz	
Spectral Range	8 μm to 14 μm	
Focus Range	Athermalized, focus-free	
Sensitivity	<50mK	
Thermal Image Settings	Auto AGC, Dynamic Detail Enhancement (DDE), Brightness, Sharpness, Contrast	
Thermal AGC Region of Interest (ROI)	Default, Presets and User Defined for optimal image quality of subjects of interest	
Image Uniformity Optimization	Automatic Flat Field Correction (FFC) - Thermal and Temporal triggers	
<b>Video</b>		
Composite Video (NTSC or PAL)	Hybrid system with IP & analog video	
Digital Video Compression	Two independent channels of H.264 and MJPEG	
Streaming Resolution PAL/NTSC	Native: 320x256	VGA: 640x480 & QVGA: 320x240
Analytics Management	Web-based configuration and management, Masking of analytic detection areas, adjustable sensitivity, automatic responses, remote I/O control	
Analytics Features	Region Entrance/Intrusion Detection, Crossover/Fence Trespassing; Auto/Manual Depth Setup, Human and Vehicle Rules, Hand-off target to autonomous PTZ tracking, Tampering Detection	
<b>System Integration</b>		
Ethernet	10/100 Mbps	
External Analytics Compatible	Yes	
Network Protocols	IPv4, HTTP, Bonjour, UPnP, DNS, NTP, RTSP, RTCP, RTP, TCP, UDP, ICMP, IGMP, DHCP, ARP	
Network APIs	Nexus SDK for comprehensive system control and integration; Nexus CGI for http command interfaces; ONVIF Profile S	
<b>General</b>		
Dimensions (L, W, H)	285 x 96 x 94 mm/11.1" x 3.8" x 3.7" With sunshield and fully extended mounting arm	
Dry Contacts (I/O)	Input: 1 relay contact Output: 1 relay contact, 300V AC / DC at 130 mA max connection terminal block	
Input Voltage	12V DC / 24V AC / PoE	
Power Consumption	12V DC: 17 W (maximum with heaters) / 24V AC: 13 VA (maximum with heaters) 24V DC: 13 W (maximum with heaters) / PoE: 13 W	
<b>Environmental</b>		
IP Rating (Dust & Water Ingress)	IP66	
Operating Temperature Range	-40° to 50° C (-40° to 122° F) Cold Start	
Storage Temperature Range	-40° to 70° C (-40° to 158° F)	
Humidity	10%-90% relative humidity	
Regulatory	FCC Part 15 (Subpart B, Class A), CE marked, EN55032, EN55024, RoHS, WEEE	

Optics				
Model	FOV	F#	Focal Length	Pixel Pitch
FB-393 ID	93°	F1.3	3.7 mm	17 μm
FB-349 ID	49°	F1.3	6.8 mm	17 μm
FB-324 ID	24°	F1.0	12.8 mm	17 μm
FB-312 ID	12°	F1.0	18 mm	12 μm
FB-309 ID	9°	F1.0	24 mm	12 μm
FB-695 ID	95°	F1.1	4.9 mm	12 μm
FB-650 ID	50°	F1.0	8.7 mm	12 μm
FB-632 ID	32°	F1.0	14 mm	12 μm
FB-618 ID	18°	F1.0	24 mm	12 μm



亦则（北京）系统技术有限公司  
 全国咨询热线：010-52878577  
 网址：www.eze.net.cn  
 邮箱：lixiaohong@eze.net.cn/  
 panwenzhong@eze.net.cn  
 联系电话：13910603180/  
 13810629767

